

AGRIMAX V-FLECTO

TIRE SIZE	VF 710/60 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	171 D



DIMENSIONES IS STANDARD

SW (MM)	720	RIM REC	DW 25 B
OD (MM)	1625	RIM ALT	DW 24 B; DW 27 B
SLR (MM)	701	ECE	E11-106R-0010832
RC (MM)	4801	SRI	775

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2740	3185	3690	4140	4585	5035	5595
FROM 65 TO 40	3010	3505	4055	4550	5040	5535	6150
30	3070	3570	4135	4635	5140	5640	6270
20	3130	3645	4220	4730	5240	5755	6395
10	3310	3855	4460	5005	5545	6085	6765
*UPTO 10 CYC WITH FRONT LOADER	4215	4905	5680	6370	7060	7745	8610
10HT	3070	3570	4135	4635	5140	5640	6270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.