


AGRIMAX V-FLECTO



TIRE SIZE	VF 650/85 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	183 D

DIMENSIONS US STANDARD

USA CODE	94515875	RC (IN)	252.5
SW (IN)	26.8	RIM REC	DW 23 B
OD (IN)	85.0	RIM ALT	DW20B;DW21B
SLR (IN)	36.9	ECE	E11-106R-0011307

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	8770	10170	11570	13160	14560	15960	17550
FROM 40 TO 25	9640	11190	12730	14460	16000	17550	19290
20	9830	11410	12980	14750	16320	17900	19680
12	10030	11630	13240	15050	16640	18250	20060
5	10600	12300	14000	15910	17600	19300	21220
UPTO 20 CYC	10950	12690	14440	16410	18170	19920	21890
UPTO 10 CYC	13060	15160	17240	19600	21680	23780	26130
UPTO 5CYC	14320	16600	18890	21470	23760	26060	28640
5 HT	9830	11410	12980	14750	16320	17900	19680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.