


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>280/85 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	115 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94021536	<b>RC (IN)</b>	126.9
<b>SW (IN)</b>	11.5	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	42.8	<b>RIM ALT</b>	W 9
<b>SLR (IN)</b>	19.4	<b>ECE</b>	E4-106R-000611

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	1480	1720	1960	2200	2450	2680
<b>25</b>	1480	1720	1960	2200	2450	2680
<b>20</b>	1590	1850	2110	2370	2620	2880
<b>5 LT</b>	1980	2300	2620	2950	3270	3590
<b>5 HT</b>	1590	1850	2110	2370	2620	2880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.