

# FL 630 SUPER

<b>TIRE SIZE</b>	<b>580/65 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	РАЗБРАСЫВАТЕЛЬ / АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94045037	<b>RC (IN)</b>	159.8
<b>SW (IN)</b>	22.7	<b>RIM REC</b>	AG 18.00
<b>OD (IN)</b>	52.2	<b>RIM ALT</b>	AG 16.00; AG 17.00; AG 20.00
<b>SLR (IN)</b>	23.4	<b>ECE</b>	E4-106R-001416

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	3440	3980	4520	5380	6350	7260	8070	9030	9890	10750
40	3750	4330	4920	5840	6900	7890	8760	9820	10760	11680
30	4530	5240	5940	7080	8340	9560	10610	11880	13020	14140
25	5090	5890	6680	7950	9380	10740	11930	13360	14630	15890
15	5910	6830	7760	9240	10900	12470	13860	15510	16990	18460
5	6730	7790	8840	10520	12410	14200	15770	17670	19360	21030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.