

RIDEMAX FL 693 M



| | |
|---------------------|--|
| TIRE SIZE | VF 400/45 R 17.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 142 D |

РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94069323 | RC (IN) | 96.4 |
| SW (IN) | 15.7 | RIM REC | 14.00 |
| OD (IN) | 31.5 | ECE | E11-106R-007199 |
| SLR (IN) | 14.1 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|------|------|------|-------|
| 45 | 2290 | 2780 | 3100 | 3570 | 4060 | 4420 | 4850 | 5320 |
| 40 | 2510 | 3040 | 3390 | 3920 | 4440 | 4850 | 5320 | 5840 |
| 30 | 3050 | 3680 | 4110 | 4750 | 5380 | 5870 | 6450 | 7080 |
| 25 | 3430 | 4130 | 4620 | 5330 | 6040 | 6600 | 7240 | 7950 |
| 20 | 3800 | 4600 | 5130 | 5920 | 6710 | 7330 | 8040 | 8830 |
| 15 | 3980 | 4810 | 5370 | 6190 | 7020 | 7670 | 8410 | 9240 |
| 5 | 4530 | 5480 | 6110 | 7050 | 8000 | 8730 | 9580 | 10520 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.