


# AGRIMAX FORCE



<b>TIRE SIZE</b>	<b>IF 600/70 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	603	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1551	<b>RIM ALT</b>	DW 20 B
<b>SLR (MM)</b>	694	<b>ECE</b>	E4-106R-000795
<b>RC (MM)</b>	4654	<b>SRI</b>	725

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2135	2455	2820	3185	3545	3910	4275	4550
<b>FROM 65 TO 40</b>	2350	2700	3100	3500	3900	4300	4700	5000
30	2440	2805	3220	3640	4055	4470	4885	5200
20	2535	2915	3345	3780	4210	4640	5075	5400
10	2980	3425	3935	4445	4950	5460	5965	6350
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	3290	3780	4340	4900	5460	6020	6580	7000
10 HT	2440	2805	3220	3640	4055	4470	4885	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.