


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 480/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTORSTARK TRAKTOR / TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	153 D

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94512775	<b>RC (IN)</b>	171.4
<b>SW (IN)</b>	19.5	<b>RIM REC</b>	W 18 L
<b>OD (IN)</b>	56.3	<b>RIM ALT</b>	W 16 L; DW 18 L
<b>SLR (IN)</b>	25.4	<b>ECE</b>	E11-106R-0010762

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4020	4670	5330	6000	6660	7320
<b>FROM 40 TO 25</b>	4420	5150	5860	6590	7320	8050
20	4510	5250	5990	6720	7460	8200
12	4600	5350	6110	6860	7610	8370
5	4860	5650	6460	7250	8050	8850
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	6190	7210	8220	9240	10250	11260
10HT	4510	5250	5990	6720	7460	8200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.