


# RIDEMAX FL 615



	<b>800/65 R 32</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	RÖMORK / TANKER / YAYICI / UYGULAMALI MAKINE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
	185 D

## UNDEFINED IS STANDARD

<b>SW (MM)</b>	830	<b>RIM REC</b>	DW 27 B
<b>OD (MM)</b>	1853	<b>ECE</b>	E11-106R-007528
<b>SLR (MM)</b>	834	<b>SRI</b>	875
<b>RC (MM)</b>	5624		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6
65	3980	4350	5275	5830	6755	7680	8420	9250
50	4815	5265	6385	7055	8175	9295	10190	11195
40	5410	5915	7175	7930	9185	10445	11450	12580
30	6010	6570	7965	8805	10200	11600	12715	13970
25	6285	6870	8335	9210	10670	12135	13300	14615
10	7160	7830	9495	10490	12155	13820	15155	16650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.