

AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 7.50 - 16 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER |
| VERSION | HD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 99 A8 |
| LI/SS FREE ROLLING | 112 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|--|
| USA CODE | 94043026 | RC (IN) | 97.4 |
| SW (IN) | 8.2 | RIM REC | 5.50 F |
| OD (IN) | 31.6 | RIM ALT | 4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F |
| SLR (IN) | 14.6 | ECE | E11-106R-004337 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 46 |
|-----------|------|
| 5 FR | 3460 |
| 15 FR | 2940 |
| 20 FR | 2770 |
| 25 FR | 2470 |
| 5 DW | 2390 |
| 15 DW | 2030 |
| 20 DW | 1920 |
| 25 DW | 1710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.