


FORESTMAX

TIRE SIZE	650/65 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR / PORTEUR
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	172 A8 ; 186 A2



DIMENSIONS IS STANDARD

SW (MM)	645	RIM REC	DW 20 B
OD (MM)	1811	RIM ALT	DW21B; DW23B
SLR (MM)	832	ECE	E11-106R-0011042
RC (MM)	5467	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
50	3050	3290	3520	3860	4165	4370	4520	4765	4930	5105	5285	5500	5670
40	3390	3655	3910	4285	4630	4855	5020	5295	5475	5670	5870	6115	6300
30	3630	3915	4190	4590	4955	5195	5375	5670	5865	6075	6285	6545	6745
25	3760	4060	4345	4760	5140	5390	5575	5880	6080	6300	6515	6790	6995
20	4170	4495	4810	5270	5695	5970	6175	6510	6735	6975	7220	7520	7750
15	4540	4900	5245	5745	6205	6505	6730	7095	7340	7605	7870	8195	8445
10	5110	5510	5900	6460	6980	7315	7570	7980	8260	8550	8850	9215	9500
10 FORESTRY SERVICE	-	-	-	-	-	-	-	-	-	-	-	-	7750
0 FORESTRY SERVICE	-	-	-	-	-	-	-	-	-	-	-	-	14490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.