


# EARTHMAX SR 45 PLUS

|              |  |
|--------------|--|
| TIRE SIZE    | 33.00 R 51   |
| UM           | IS STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | DUMPER RÍGIDO  |
| VERSÃO       | HEAT RESISTANT COMPOUND  |
| TIRE TYPE    | TL   |
| LI/SS        | 235 B  |



## DIMENSÕES IS STANDARD

|          |           |             |    |
|----------|-----------|-------------|----|
| OD (MM)  | 3065      | TRA CODE    | E4 |
| SLR (MM) | 1369      | STAR RATING | ★★ |
| RC (MM)  | 9313      |             |    |
| RIM REC  | 24.00/5.0 |             |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 30000 | 30750 | 32500 | 33500 | 34500 | 35500 | 36500 | 37500 | 38750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.