



PRINTED ON  
22-04-2026

## DATA SHEET

# PL 801

|                     |                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>300 - 15</b>                                                                         |
| <b>UM</b>           | IS STANDARD                                                                             |
| <b>CONSTRUCTION</b> |                                                                                         |
| <b>MACHINERY</b>    | ROTOR RAKE/ TEDDER / HAY<br>HARVESTER / FORKLIFT / HARVESTER<br>/ IMPLEMENTS / FORKLIFT |
| <b>VERSION</b>      | STANDARD                                                                                |
| <b>TIRE TYPE</b>    | TT                                                                                      |



## DIMENSIONS IS STANDARD

|                |         |            |                 |
|----------------|---------|------------|-----------------|
| <b>SW (MM)</b> | 295     | <b>ECE</b> | E11-106R-007161 |
| <b>OD (MM)</b> | 840     | <b>PR</b>  | 18              |
| <b>RIM REC</b> | 8.00 BD |            |                 |
| <b>RIM ALT</b> | 8.0     |            |                 |

## LOAD CAPACITY (KG/TIRE)

|                           |             |
|---------------------------|-------------|
| <b>KM/H / BAR</b>         | <b>7.50</b> |
| <b>25 LOAD WHEEL</b>      | 5850        |
| <b>25 STEER WHEEL</b>     | 4500        |
| <b>10 OTHER VEHICLES</b>  | 5850        |
| <b>25 OTHER VEHICLES</b>  | 4500        |
| <b>STATIC SIDE LOADER</b> | 6795        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.