

MINE STAR



MINE STAR



MINE STAR is a bias-ply tire which is an excellent choice for heavy-duty underground mining operations. It features high cut/chip and puncture resistance providing improved operational efficiency. MINE STAR is made of a special compound and features a special tread design resulting in an extended tire life-cycle.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø15"	38X16 -15	TT	-	32		11.5	-	0		990	0	0	28,5	STD
	35X15 -15	TT	-	32	-	11.0	11.50 11.00 BD	0		885	0	0	23,5	STD
	8.25 - 15	TT	-	20	-	6.5	6.0 7.0	0		848	0	0	19	STD
	35X15 -15	TT	-	20	-	11.0	11.50 11.00 BD	0		885	0	0	23,5	STD
	35X15 -15	TL	-	32	-	11.0	11.50 11.00 BD	0		885	0	0	23,5	STD

STD: STANDARD

TECHNOLOGIES			PERFORMANCES		
					Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index
					

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION	
					REC RIM	ALT RIM								
														
32X14.50/15 -15	TT	-	28		11.0	11.50 11.00 BD 10.50	0		825	0	0	23,5	STD	
38X16 -15	TL	-	32		11.5	-	0		990	0	0	28,5	STD	
Ø25"	55X19.00 -25	TL	L5	50	-	14.00	-	0		1400	632	4280	69	STD
Ø34"	55X19.00 -34	TL	L5	50	-	16.00	-	0		1435			64	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			  
			

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index