


# EARTHMAX SR 57

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>10.00 R 15</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BULLDOZER / CHARGEUR-<br>TRANSPORTEUR LHD / CHARGEUR                                     |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSIONS US STANDARD

|                 |          |                    |    |
|-----------------|----------|--------------------|----|
| <b>CODE USA</b> | 94065615 | <b>TRA CODE</b>    | L5 |
| <b>OD (IN)</b>  | 36.1     | <b>STAR RATING</b> | ★  |
| <b>RIM REC</b>  | 7.50     |                    |    |
| <b>RIM ALT</b>  | 7.00     |                    |    |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>102</b> |
| 3.7              | 7720       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.