


# FL 630 ULTRA

<b>TIRE SIZE</b>	<b>800/45 R 26.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ÉPANDEUR / VÉHICULE CITERNE / REMORQUE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D ; 184 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	828	<b>RIM REC</b>	AG 28.00
<b>OD (MM)</b>	1393	<b>RIM ALT</b>	AG 24.00
<b>SLR (MM)</b>	618	<b>ECE</b>	E11-106R-004074
<b>RC (MM)</b>	4238	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1955	2230	2505	3115	3540	4090	4640	5065	5555	6100
65	2145	2450	2750	3420	3890	4490	5095	5565	6100	6700
50	2600	2965	3330	4140	4705	5435	6165	6735	7385	8110
40	2880	3285	3690	4590	5220	6030	6840	7470	8190	9000
30	3240	3695	4150	5165	5870	6785	7695	8400	9210	10120
25	3390	3870	4345	5405	6145	7100	8050	8790	9640	10590
10	3860	4405	4945	6155	6995	8085	9170	10010	10975	12060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.