


RIDEMAX FL 693 M

TIRE SIZE	560/60 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	169 D



DIMENSIONES IS STANDARD

SW (MM)	543	RIM REC	AG 16.00
OD (MM)	1244	RIM ALT	16.00; 17.00; AG 20.00
SLR (MM)	552	ECE	E11-106R-006650
RC (MM)	3767	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	1745	2165	2380	2750	3120	3435	3750	4120	4650	5280
65	1915	2380	2610	3020	3425	3770	4120	4525	5105	5800
50	2320	2880	3160	3655	4145	4565	4985	5480	6180	7020
40	2605	3235	3555	4105	4660	5130	5605	6155	6945	7890
25	3025	3760	4125	4770	5410	5960	6510	7150	8070	9165
10	3450	4285	4700	5430	6160	6790	7415	8145	9190	10440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.