

FLOTATION 648

TIRE SIZE	500/50 - 17
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	137 A8/133 B
LI/SS FREE ROLLING	149 A8/145 B



DIMENSÕES US STANDARD

CÓDIGO USA	94039807	RC (IN)	108.3
SW (IN)	20.1	RIM REC	16.00
OD (IN)	37.2	ECE	E4-106R-001885
SLR (IN)	16.4	PR	14

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	32	35	41
5 FR	8710	9170	10030
10 FR	7840	8240	9030
20 FR	6970	7330	8020
25 FR	6220	6550	7160
30 FR	5600	5900	6390
5 DW	6160	6480	7100
10 DW	5540	5830	6390
20 DW	4930	5180	5680
25 DW	4400	4630	5070
30 DW	3960	4170	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.