


AW 711

| | |
|---------------------|--|
| TIRE SIZE | 265/70 R 16.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COSECHADORA / MAQUINARIA AGRÍCOLA / COSECHADORA / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STUBBLE RESISTANT |
| TIRE TYPE | TL |
| LI/SS | 134 A8/B |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 264 | RIM REC | 8.25 |
| OD (MM) | 773 | ECE | E11-106R-002978 |
| SLR (MM) | 343 | SRI | 370 |
| RC (MM) | 2286 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|-----|------|------|------|------|------|------|------|------|
| 50 | 680 | 895 | 1085 | 1255 | 1445 | 1635 | 1760 | 1930 | 2120 |
| 40 | 680 | 895 | 1085 | 1255 | 1445 | 1635 | 1760 | 1930 | 2120 |
| 30 | 760 | 1000 | 1215 | 1405 | 1615 | 1830 | 1975 | 2165 | 2375 |
| 25 | 810 | 1065 | 1290 | 1490 | 1720 | 1945 | 2100 | 2300 | 2525 |
| 20 | 860 | 1125 | 1365 | 1580 | 1820 | 2060 | 2225 | 2435 | 2675 |
| 10 | 955 | 1250 | 1515 | 1755 | 2020 | 2290 | 2470 | 2705 | 2970 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.