

# AW 711

<b>TIRE SIZE</b>	<b>400/60 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94045235	<b>RC (IN)</b>	110.5
<b>SW (IN)</b>	15.5	<b>RIM REC</b>	14
<b>OD (IN)</b>	37.2	<b>RIM ALT</b>	13
<b>SLR (IN)</b>	16.5	<b>ECE</b>	E4-106R-001397

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	55	58	73	80
30	2690	3490	4300	4930	5730	6540	6980	7690	8060	8410	8940	9650
25	2690	3490	4300	4930	5730	6540	6980	7690	8060	8410	8940	9650
20	3010	3910	4820	5510	6420	7320	7830	8620	9030	9420	10020	10800
15	3200	4160	5110	5860	6820	7780	8310	9160	9590	10020	10650	11490
10	3380	4400	5420	6210	7220	8230	8800	9700	10150	10600	11280	12160
5	3760	4890	6020	6890	8020	9150	9780	10770	11280	11770	12520	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.