

MULTIMAX MP 513

| | |
|---------------------|---|
| TIRE SIZE | 495/70 R 24 MPT |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ / ТЕХНИКА ДЛЯ ВНЕСЕНИЯ УДОБРЕНИЙ / УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 G |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|--------------------------|
| SW (MM) | 499 | RIM REC | W 16 L |
| OD (MM) | 1304 | RIM ALT | DW 15 L; DW 16 L; W 15 L |
| SLR (MM) | 588 | ECE | E4-54R-0029057 |
| RC (MM) | 3974 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.5 | 3.0 | 3.5 |
|------------|------|------|------|------|------|
| 90 | 1980 | 2340 | 2840 | 3250 | 3875 |
| 65 | 2150 | 2540 | 3085 | 3530 | 4205 |
| 40 | 2280 | 2695 | 3270 | 3740 | 4460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.