


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>420/85 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	144 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94033140	<b>RC (IN)</b>	197.4
<b>SW (IN)</b>	17.2	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	66.1	<b>RIM ALT</b>	W 13; W 14 L
<b>SLR (IN)</b>	30.0	<b>ECE</b>	E4-106R-000661

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	3390	3960	4510	5070	5620	6150
<b>25</b>	3390	3960	4510	5070	5620	6150
<b>20</b>	3640	4230	4830	5420	6020	6610
<b>5 LT</b>	4560	5300	6050	6790	7540	8280
<b>5 HT</b>	3640	4230	4830	5420	6020	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.