

TR 882

TIRE SIZE	400/60 - 15.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
VERSION	ARAMID BELTED HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	400	RIM REC	AG 13.00
OD (MM)	875	ECE	E11-106R-005354
SLR (MM)	378	PR	18
RC (MM)	2605	SRI	410

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250
10 DW	3220
25 DW	2735
30 DW	2575
40 DW	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.