


# EARTHMAX SR 25 PLUS

<b>TIRE SIZE</b>	<b>14.00 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOTONIVELADORA / CARREGADORA / TRATOR DE ESTEIRA / CARREGADORA / MOTONIVELADORA / TRATOR DE ESTEIRA
<b>VERSÃO</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	153 A8 ; 175 A2



## DIMENSÕES IS STANDARD

<b>OD (MM)</b>	1372	<b>RIM ALT</b>	9.00GR
<b>SLR (MM)</b>	626	<b>TRA CODE</b>	G2/L2
<b>RC (MM)</b>	4146	<b>STAR RATING</b>	★
<b>RIM REC</b>	8.00TG		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	5.25	5.50
40	2240	2430	2650	2800	3000	3250	3350	3650	-	-
10	-	-	-	-	-	-	-	-	6700	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.