DATA SHEET

PRINTED ON
22-04-2026

AS 504

TIRE SIZE	**7.00 - 12**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	SOLLEVATORE TELESCOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESCOPICO
VERSIONE	ARAMID BELTED
TIRE TYPE	TL
LI/SS DRIVE WHEEL	88 A8
LI/SS FREE ROLLING	100 A8

DIMENSIONI IS STANDARD

SW (MM)	187	**RIM REC**	4.5
OD (MM)	683	**ECE**	E11-106R-003382
SLR (MM)	311	**PR**	8
RC (MM)	2049		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.30
10 FR	1120
25 FR	950
30 FR	895
40 FR	800
10 DW	785
25 DW	665
30 DW	625
40 DW	560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..