


# FL 630 ULTRA

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>710/50 R 26.5</b>                                                                     |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPREADER / TANKER / TRAILER /<br>IMPLEMENTS                                              |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TL/TT</b>        | TL                                                                                       |
| <b>LI/SS</b>        | 170 D ; 181 A8                                                                           |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94047284 | <b>RC (IN)</b> | 165.7           |
| <b>SW (IN)</b>  | 28.6     | <b>RIM REC</b> | AG 24.00        |
| <b>OD (IN)</b>  | 54.4     | <b>RIM ALT</b> | AG 20.00        |
| <b>SLR (IN)</b> | 23.6     | <b>ECE</b>     | E11-106R-006812 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 15   | 17   | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 3860 | 4400 | 4940 | 6140  | 6990  | 8070  | 9150  | 10000 | 10960 | 12040 |
| 40        | 4230 | 4830 | 5420 | 6750  | 7670  | 8860  | 10050 | 10980 | 12040 | 13230 |
| 30        | 5130 | 5850 | 6570 | 8170  | 9290  | 10720 | 12170 | 13290 | 14570 | 16000 |
| 25        | 5820 | 6650 | 7460 | 9280  | 10550 | 12190 | 13820 | 15100 | 16560 | 18190 |
| 15        | 6690 | 7640 | 8580 | 10660 | 12120 | 14010 | 15880 | 17350 | 19020 | 20900 |
| 5         | 7630 | 8700 | 9700 | 12150 | 13810 | 15960 | 18100 | 19760 | 21670 | 23810 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.