

AGRIMAX RT 855

TIRE SIZE	520/85 R 42
UM	IS STANDARD
MACHINERY	PULVERIZADOR / VENDIMIADORA / TRACTOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	SPECIAL
TIRE TYPE	TL
LI/SS	157 A8/B



DIMENSIONES IS STANDARD

SW (MM)	516	ECE	E4-106R-000792
OD (MM)	1951	SRI	925
SLR (MM)	858	TRA CODE	R1W
RC (MM)	5782	TREAD DEPTH (MM)	56,5
RIM REC	DW 16 L ; W 16 A ; DD 16	TKPH (TK/H)	0
RIM ALT	DW 18 A ; DD 18 ; W 18 A ; DD 18 L		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	2270	2640	3015	3385	3755	4125
40	2270	2640	3015	3385	3755	4125
30	2430	2830	3225	3625	4020	4415
10 LT	3045	3540	4040	4535	5035	5530
10 HT	2430	2830	3225	3625	4020	4415

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.