

# AGRIMAX RT 765

|              |                                                                                                    |
|--------------|----------------------------------------------------------------------------------------------------|
| TIRE SIZE    | 650/75 R 42                                                                                        |
| UM           | IS STANDARD                                                                                        |
| CONSTRUCTION |  RADIAL           |
| MACHINERY    | FELDSPRITZE / TRACTOR /<br>TRAUBENERNTEMASCHINE /<br>ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION      | STANDARD                                                                                           |
| TIRE TYPE    | TL                                                                                                 |
| LI/SS        | 170 D                                                                                              |



## ABMESSUNGEN IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 655  | RIM REC | DW21B           |
| OD (MM)  | 2043 | RIM ALT | DW20B;DW23B     |
| SLR (MM) | 916  | ECE     | E11-106R-006402 |
| RC (MM)  | 6147 | SRI     | 975             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 2820 | 3240 | 3720 | 4200 | 4680 | 5160 | 5640 | 6000 |
| 50         | 2965 | 3405 | 3910 | 4410 | 4915 | 5420 | 5925 | 6300 |
| 40         | 3090 | 3550 | 4075 | 4600 | 5125 | 5655 | 6180 | 6570 |
| 30         | 3245 | 3730 | 4280 | 4830 | 5385 | 5935 | 6490 | 6900 |
| 10 LT      | 3780 | 4345 | 4985 | 5630 | 6275 | 6915 | 7560 | 8040 |
| 10 HT      | 3245 | 3730 | 4280 | 4830 | 5385 | 5935 | 6490 | 6900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.