


# AS 504

<b>TIRE SIZE</b>	7.5L - 15
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	HD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	100 A8
<b>LI/SS FREE ROLLING</b>	113 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94040711	<b>RC (IN)</b>	89.8
<b>SW (IN)</b>	8.3	<b>RIM REC</b>	6 LB
<b>OD (IN)</b>	30.1	<b>RIM ALT</b>	5 K; 5½ J; 5½ K
<b>SLR (IN)</b>	13.9	<b>ECE</b>	E11-106R-004240

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54
5 FR	3550
15 FR	3020
20 FR	2840
25 FR	2540
5 DW	2470
15 DW	2090
20 DW	1970
25 DW	1760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.