


# MULTIMAX MP 527

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>360/70 R 18 IND</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | COMPACT LOADER / TELEHANDLER /<br>COMPACT LOADER / TELEHANDLER                           |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 142 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                                  |
|-----------------|----------|----------------|----------------------------------|
| <b>USA CODE</b> | 94053650 | <b>RC (IN)</b> | 113.7                            |
| <b>SW (IN)</b>  | 14.2     | <b>RIM REC</b> | 11                               |
| <b>OD (IN)</b>  | 38.1     | <b>RIM ALT</b> | W10 ; 11 SDC ; W11 ; 12 ; 12 SDC |
| <b>SLR (IN)</b> | 17.3     | <b>ECE</b>     | E11-106R-002996                  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23   | 29   | 35   | 41   | 46   | 51    | 58    | 61    | 64    |
|-----------|------|------|------|------|------|-------|-------|-------|-------|
| 30        | 2810 | 3340 | 3800 | 4330 | 4850 | 5200  | 5840  | -     | -     |
| 25        | 2810 | 3340 | 3800 | 4330 | 4850 | 5200  | 5840  | -     | -     |
| 20        | 3010 | 3570 | 4080 | 4640 | 5200 | 5580  | 6260  | -     | -     |
| 15        | 3120 | 3700 | 4220 | 4810 | 5390 | 5790  | 6490  | -     | -     |
| 5 CYC.    | 3430 | 4210 | 4960 | 5700 | 6490 | 7050  | 7980  | 8420  | 8760  |
| STATIC    | 5250 | 6460 | 7590 | 8740 | 9950 | 10820 | 12230 | 12910 | 13440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.