

# TR 319

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 29 - 15   |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | IMPLEMENT MACHINERY / ORCHARD HARVESTER / TRENCHER / HARVESTER / IMPLEMENTS |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 106 B   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 312  | <b>RIM REC</b> | 10 LB           |
| <b>OD (MM)</b>  | 755  | <b>ECE</b>     | E11-106R-004605 |
| <b>SLR (MM)</b> | 360  | <b>PR</b>      | 8               |
| <b>RC (MM)</b>  | 2264 |                |                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.10</b> |
| 50                | 950         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.