

# AGRIMAX RT 765

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>620/70 R 38</b>                                                              |
| <b>UM</b>        | US STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / TRACTOR /<br>VENDIMIADORA / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | STANDARD                                                                        |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 170 D                                                                           |



## DIMENSIONES US STANDARD

|                   |          |                |                  |
|-------------------|----------|----------------|------------------|
| <b>CÓDIGO USA</b> | 94063482 | <b>RC (IN)</b> | 220.1            |
| <b>SW (IN)</b>    | 24.6     | <b>RIM REC</b> | DW 20 B          |
| <b>OD (IN)</b>    | 72.2     | <b>RIM ALT</b> | DW 18 L ; W 18 L |
| <b>SLR (IN)</b>   | 32.6     | <b>ECE</b>     | E11-106R-005997  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17    | 20    | 23    | 29    | 35    | 41    | 47    |
|-------------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| <b>40</b>   | 5160 | 6080 | 7010 | 7800  | 8730  | 9520  | 10450 | 11240 | 12300 | 13230 |
| <b>30</b>   | 5420 | 6390 | 7360 | 8200  | 9170  | 10010 | 10980 | 11810 | 12920 | 13890 |
| <b>25</b>   | 5650 | 6670 | 7680 | 8550  | 9570  | 10440 | 11450 | 12310 | 13480 | 14480 |
| <b>20</b>   | 5940 | 7000 | 8070 | 8980  | 10040 | 10960 | 12030 | 12930 | 14150 | 15210 |
| <b>5 LT</b> | 6920 | 8160 | 9400 | 10460 | 11710 | 12760 | 14010 | 15070 | 16490 | 17720 |
| <b>5 HT</b> | 5940 | 7000 | 8070 | 8980  | 10040 | 10960 | 12030 | 12930 | 14150 | 15210 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.