


# FORESTMAX

<b>TIRE SIZE</b>	<b>600/60 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / FORESTRY
<b>VERSION</b>	STEEL BELTED
<b>TL/TT</b>	TL
<b>LI/SS</b>	152 A8 ; 149 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	570	<b>RIM REC</b>	DW18L
<b>OD (MM)</b>	1431	<b>RIM ALT</b>	DW20B
<b>SLR (MM)</b>	655	<b>ECE</b>	E11-106R-0010523
<b>RC (MM)</b>	4315	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4
50	2210	2470	2535	2795	3020	3120	3250
40	2415	2700	2770	3055	3300	3410	3550
30	2585	2890	2965	3270	3535	3650	3800
25	2685	3000	3080	3395	3670	3790	3945
20	2975	3325	3410	3760	4065	4200	4370
15	3240	3620	3715	4095	4425	4570	4760
10	3625	4050	4155	4580	4950	5115	5325
<b>10 FORESTRY SERVICE</b>	-	-	-	-	-	-	4370
<b>0 FORESTRY SERVICE</b>	-	-	-	-	-	-	8165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.