


POWERTRAILER SR 331



| | |
|---------------------|--|
| TIRE SIZE | 560/60 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | REMOLQUE / MAQUINARIA AGRÍCOLA / CAMIÓN CISTERNA |
| VERSIÓN | IMPLEMENT |
| TIRE TYPE | TL |
| LI/SS | 169 D |

DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CÓDIGO USA | 94075997 | RIM REC | AG 16.00 |
| OD (IN) | 49.0 | RIM ALT | 17.00; AG18.00 |
| SLR (IN) | 22.2 | ECE | E11-106R-0010147 |
| RC (IN) | 148.6 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH/PSI | 46 | 52 | 58 | 65 | 73 | 80 | 87 |
|---------|-------|-------|-------|-------|-------|-------|-------|
| 5 | 14960 | 16340 | 17960 | 19100 | 20250 | 21640 | 23020 |
| 15 | 13130 | 14340 | 15760 | 16770 | 17780 | 18990 | 20210 |
| 25 | 11300 | 12350 | 13570 | 14430 | 15300 | 16350 | 17390 |
| 30 | 10050 | 10990 | 12070 | 12840 | 13610 | 14540 | 15480 |
| 40 | 8310 | 9080 | 9970 | 10610 | 11250 | 12020 | 12800 |
| 43 | 7560 | 8260 | 9070 | 9660 | 10240 | 10930 | 11640 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.