


# AS 504

<b>TIRE SIZE</b>	<b>10.0/75 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	111 A8
<b>LI/SS FREE ROLLING</b>	123 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	264	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	785	<b>ECE</b>	E4-106R-001812
<b>SLR (MM)</b>	360	<b>PR</b>	10
<b>RC (MM)</b>	2404	<b>SRI</b>	360

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.90
10 FR	2170
25 FR	1845
30 FR	1735
40 FR	1550
10 DW	1525
25 DW	1295
30 DW	1220
40 DW	1090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.