


# EARTHMAX SR 22



**14.00 R 24**

|                     |  |
|---------------------|--|
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | GREYDER / YÜKLEYICI / DOZER /<br>YÜKLEYICI / DOZER / GREYDER                             |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 153 A8 ; 175 A2  |

## UNDEFINED US STANDARD

|                 |          |                    |                   |
|-----------------|----------|--------------------|-------------------|
| <b>USA CODE</b> | 94048816 | <b>RIM REC</b>     | 8.00 TG           |
| <b>OD (IN)</b>  | 53.9     | <b>RIM ALT</b>     | 9.00 GR; 10.00 VA |
| <b>SLR (IN)</b> | 24.6     | <b>TRA CODE</b>    | G2/L2             |
| <b>RC (IN)</b>  | 163.0    | <b>STAR RATING</b> | ★                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 29   | 33   | 36   | 40   | 44   | 47   | 51   | 54   | 76    | 80    |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 25        | 4940 | 5360 | 5840 | 6150 | 6600 | 7150 | 7400 | 8050 | -     | -     |
| 5         | -    | -    | -    | -    | -    | -    | -    | -    | 14800 | 15200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.