


# TF 8181

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>4.00 - 16</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRATTORE 2WD / TRATTORE / RIMORCHIO  |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 61 A8  |



## DIMENSIONI US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CODICE USA</b> | 94036400 | <b>RC (IN)</b> | 73.9           |
| <b>SW (IN)</b>    | 4.4      | <b>RIM REC</b> | 3.00 D         |
| <b>OD (IN)</b>    | 24.8     | <b>ECE</b>     | E4-106R-002183 |
| <b>SLR (IN)</b>   | 11.9     | <b>PR</b>      | 4              |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>50</b> |
| 25               | 570       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.