

# EARTHMAX SR 55

<b>TIRE SIZE</b>	<b>29.5 R 29</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	БУЛЬДОЗЕР / ПОГРУЗОЧНО-ДОСТАВОЧНАЯ МАШИНА / ПОГРУЗЧИК
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	223 A2



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94515271	<b>RIM REC</b>	25.00/3.5
<b>OD (IN)</b>	79.1	<b>RIM ALT</b>	24.00/3.5; 26.00/3.5
<b>SLR (IN)</b>	35.9	<b>TRA CODE</b>	L55
<b>RC (IN)</b>	238.1	<b>STAR RATING</b>	★★★

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	73	76	80	83	87	91	94	98	102	105	109	112	116
5	43000	44100	45400	46700	49400	50700	52000	53600	55100	56800	58400	58400	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.