

# FARM HIGHWAY TOUGH

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 12.5L - 15  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ❖ BIAS  |
| <b>MACHINERY</b>    | MAȘINI DE IMPLEMENTARE /<br>REMORCĂ / MAȘINI DE<br>IMPLEMENTARE |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 134 J   |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94032525 | <b>RC (IN)</b> | 91.5            |
| <b>SW (IN)</b>  | 12.5     | <b>RIM REC</b> | 10 LB           |
| <b>OD (IN)</b>  | 32.1     | <b>ECE</b>     | E11-54R-0019049 |
| <b>SLR (IN)</b> | 14.3     | <b>PR</b>      | 12              |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>90</b> |
| 62               | 4680      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.