

AGRIMAX FORCE

TIRE SIZE	IF 650/60 R 34
UM	IS STANDARD
MACHINERY	COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	165 D



DIMENSIONES IS STANDARD

SW (MM)	650	RIM ALT	DW 21 B
OD (MM)	1644	ECE	E11-106R-006014
SLR (MM)	746	SRI	775
RC (MM)	4954	TRA CODE	R1W
RIM REC	DW 23 B	TREAD DEPTH (MM)	58,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2150	2475	2855	3185	3555	3885	4350	4685
FROM 65 TO 40	2365	2725	3140	3500	3910	4270	4785	5150
30	2455	2830	3265	3640	4065	4440	4975	5355
20	2550	2940	3390	3780	4220	4610	5165	5560
10	3000	3460	3985	4445	4965	5420	6075	6540
*UPTO 10 CYC WITH FRONT LOADER	3310	3815	4395	4900	5470	5975	6695	7210
10 HT	2455	2830	3265	3640	4065	4440	4975	5355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.