

AS 504

TIRE SIZE	15.5/80 - 24
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	148 A8
LI/SS FREE ROLLING	160 A8



РАЗМЕРЫ US STANDARD

USA CODE	94018987	RC (IN)	152.6
SW (IN)	15.1	RIM REC	W 12
OD (IN)	49.7	RIM ALT	W 13; W 14 L
SLR (IN)	22.4	ECE	E4-106R-002816

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	51
5 FR	13890
15 FR	11810
20 FR	11110
25 FR	9920
5 DW	9720
15 DW	8270
20 DW	7780
25 DW	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.