



IS standard



GROWING TOGETHER

XL GRIP (ADT)



PRODUCT DATA SHEET



Bias



XL GRIP (ADT)



XL GRIP (ADT) is a bias-ply tire for Articulated dump trucks designed to minimize cuts and punctures in severe conditions where exceptional traction is required. These features result in an extended tire life.

Performance



Cut and Chip Resistance



Durability



Hard Rocky Surface



Traction

	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	26.5 - 25	TL	E-3	32	-	STD	-	680	1740	796	5150	36	22.00/3.0	-
	26.5 - 25	TL	E-3	28	-	STD	-	680	1740	796	5150	36	22.00/3.0	-
	29.5 - 25	TL	E-3	32	-	STD	-	760	1860	849	5544	39	25.00/3.5	-
	29.5 - 25	TL	E-3	28	-	STD	-	760	1860	849	5544	39	25.00/3.5	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference