

# AS 504

**10.0/75 - 15.3****UM** US STANDARD**CONSTRUCTION**  BIAS**MACHINERY** TELESKOPIK YÜKLEYİCİ / TARLA  
RÖMORKU / UYGULAMALI MAKİNE /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

111 A8

123 A8



## UNDEFINED US STANDARD

<b>USA CODE</b>	94018567	<b>RC (IN)</b>	94.6
<b>SW (IN)</b>	10.4	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	30.9	<b>ECE</b>	E4-106R-001812
<b>SLR (IN)</b>	14.2	<b>PR</b>	10

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>57</b>
<b>5 FR</b>	4780
<b>15 FR</b>	4070
<b>20 FR</b>	3820
<b>25 FR</b>	3420
<b>5 DW</b>	3360
<b>15 DW</b>	2850
<b>20 DW</b>	2690
<b>25 DW</b>	2400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.