


AS 504

| | |
|---------------------------|---|
| TIRE SIZE | 11.5/80 - 15.3 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 123 A8 |
| LI/SS FREE ROLLING | 135 A8 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94018727 | RC (IN) | 100.0 |
| SW (IN) | 11.4 | RIM REC | 9.00 |
| OD (IN) | 34.1 | ECE | E4-106R-001894 |
| SLR (IN) | 15.0 | PR | 12 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 59 |
|-----------|------|
| 5 FR | 6720 |
| 15 FR | 5720 |
| 20 FR | 5380 |
| 25 FR | 4810 |
| 5 DW | 4780 |
| 15 DW | 4070 |
| 20 DW | 3820 |
| 25 DW | 3420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.