

# MULTIMAX MP 527

**340/80 R 18 IND****UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** KÜÇÜK YÜKLEYİCİ / TELESKOPIK  
YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

143 A8/B

**UNDEFINED IS STANDARD**

<b>SW (MM)</b>	343	<b>RIM REC</b>	11 ; 11 SDC ; W 11
<b>OD (MM)</b>	1001	<b>RIM ALT</b>	W 10 ; 12 ; 12 SDC
<b>SLR (MM)</b>	455	<b>ECE</b>	E4-106R-002981
<b>RC (MM)</b>	3028	<b>SRI</b>	475

**LOAD CAPACITY (KG/TIRE)**

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1310	1555	1775	2020	2265	2430	2725	-	-
40	1310	1555	1775	2020	2265	2430	2725	-	-
30	1405	1665	1900	2165	2425	2600	2920	-	-
25	1455	1725	1970	2240	2515	2695	3025	-	-
10 CYC.	1600	1965	2315	2660	3030	3295	3725	3930	4090
STATIC	2450	3010	3545	4080	4640	5050	5710	6020	6270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.