


# TR 171

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>12.4 - 24</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSIÓN</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 102 A8   |



## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94038916 | <b>RC (IN)</b> | 140.0           |
| <b>SW (IN)</b>    | 12.4     | <b>RIM REC</b> | W 11            |
| <b>OD (IN)</b>    | 45.9     | <b>RIM ALT</b> | W 9; W 10       |
| <b>SLR (IN)</b>   | 21.4     | <b>ECE</b>     | E11-106R-004479 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>16</b> |
| 25               | 1870      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.