

# FL 630 SUPER

<b>TIRE SIZE</b>	<b>710/50 R 26.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	727	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1383	<b>RIM ALT</b>	AG 20.00
<b>SLR (MM)</b>	626	<b>ECE</b>	E11-106R-003009
<b>RC (MM)</b>	4237	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1745	2020	2290	2780	3220	3710	4200	4525	5015	5450
65	1920	2220	2520	3060	3540	4080	4620	4980	5520	6000
50	2325	2690	3050	3705	4285	4940	5595	6030	6680	7260
40	2615	3025	3430	4165	4815	5550	6285	6775	7510	8160
25	3035	3510	3985	4835	5595	6450	7300	7870	8725	9480
10	3460	4000	4540	5510	6375	7345	8320	8965	9940	10800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.