

AGRIMAX RT 855

TIRE SIZE	340/85 R 24
UM	IS STANDARD
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	125 A8/B



РАЗМЕРЫ IS STANDARD

SW (MM)	353	RIM ALT	W 11
OD (MM)	1188	ECE	E4-106R-000604
SLR (MM)	532	SRI	575
RC (MM)	3542	TRA CODE	R1W
RIM REC	W 12	TREAD DEPTH (MM)	43,5

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	910	1060	1205	1355	1505	1650
40	910	1060	1205	1355	1505	1650
30	975	1135	1295	1455	1615	1770
10 LT	1220	1420	1620	1820	2020	2215
10 HT	975	1135	1295	1455	1615	1770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.