


# AGRIMAX SIRIO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>540/65 R 34</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MOTORSTARK TRAKTOR / TRAKTOR   |
| <b>VERSION</b>      | HIGH SPEED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 D ; 149 E  |



## DIMENSIONER US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94045297 | <b>RC (IN)</b> | 186.4          |
| <b>SW (IN)</b>  | 20.9     | <b>RIM REC</b> | W 16 L         |
| <b>OD (IN)</b>  | 61.7     | <b>RIM ALT</b> | W 18           |
| <b>SLR (IN)</b> | 28.4     | <b>ECE</b>     | E4-106R-000815 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23    | 29    | 35    |
|-----------|------|------|------|------|------|-------|-------|-------|
| 45        | 3370 | 3870 | 4440 | 5020 | 5590 | 6160  | 6670  | 7160  |
| 40        | 3680 | 4230 | 4860 | 5480 | 6110 | 6730  | 7290  | 7830  |
| 30        | 3870 | 4440 | 5100 | 5760 | 6420 | 7080  | 7650  | 8220  |
| 25        | 4030 | 4640 | 5320 | 6010 | 6690 | 7390  | 7980  | 8580  |
| 15        | 4360 | 5020 | 5760 | 6500 | 7240 | 7990  | 8640  | 9280  |
| 5         | 5520 | 6350 | 7290 | 8220 | 9160 | 10100 | 10920 | 11740 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.