


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>900/60 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOISSONNEUSE / ÉPANDEUR / TRACTEUR / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	181 A8 ; 178 B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94062423	<b>RC (IN)</b>	224.3
<b>SW (IN)</b>	35.3	<b>RIM REC</b>	DW 27 B
<b>OD (IN)</b>	74.5	<b>RIM ALT</b>	DW 28 B ; DW 30 B
<b>SLR (IN)</b>	33.1	<b>ECE</b>	E11-106R-005768

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	20	23	29	35	41	46	49	55
30	7440	8430	9590	10580	11740	13060	14050	15380	16530	-	-
25	8190	9280	10550	11640	12920	14370	15460	16920	18190	-	-
20	8760	9930	11300	12470	13820	15390	16560	18110	19470	-	-
5 LT	10970	12430	14140	15610	17310	19260	20720	22670	24370	-	-
5 HT	8760	9930	11300	12470	13820	15390	16560	18110	19470	-	-
5 CYC.	-	14910	16950	18710	20760	23090	24840	27180	29220	29680	30920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.