

# AGRIMAX V- FLECTO

VF 650/65 R 42

|              |  |
|--------------|--|
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR   |
| VERSION      | STANDARD   |
| TIRE TYPE    | TL   |
|              | 174 D  |



## UNDEFINED US STANDARD

|          |          |         |                 |
|----------|----------|---------|-----------------|
| USA CODE | 94062102 | RC (IN) | 227.3           |
| SW (IN)  | 25.6     | RIM REC | DW 23 B         |
| OD (IN)  | 75.3     | RIM ALT | DW 21 B         |
| SLR (IN) | 33.5     | ECE     | E11-106R-005713 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                     | 9     | 12    | 15    | 17    | 20    | 23    | 29    |
|-------------------------------|-------|-------|-------|-------|-------|-------|-------|
| 45                            | 6840  | 7910  | 8990  | 10210 | 11140 | 12090 | 13440 |
| FROM 40 TO 25                 | 7530  | 8710  | 9890  | 11220 | 12260 | 13290 | 14770 |
| 20                            | 7670  | 8870  | 10070 | 11440 | 12500 | 13560 | 15060 |
| 12                            | 7830  | 9050  | 10270 | 11660 | 12740 | 13820 | 15350 |
| 5                             | 8280  | 9580  | 10870 | 12330 | 13480 | 14620 | 16250 |
| *UPTO 5 CYC WITH FRONT LOADER | 10540 | 12190 | 13830 | 15710 | 17150 | 18610 | 20680 |
| 5 HT                          | 7670  | 8870  | 10070 | 11440 | 12500 | 13560 | 15060 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.